

Modified Article	Date of Application	Date of Publication
1.2 (g)	01/01/2024	01/01/2024
8	01/01/2024	01/01/2024
Table H-1	01/01/2024	01/01/2024

Any *HEADING* is for reference only and has no regulatory effect.

A capitalised and italicised word in this document is defined in the FIA International Sporting Code (Code), the National Competition Rules (NCR), including their Appendices or this document.

1. GENERAL

Each *Automobile* in an *Event* as detailed, except where noted in specific Group/category/class regulations, must be equipped with a fire extinguisher which complies with the following conditions.

Halon extinguishers (1201 or 1311, including BCF) are not permitted under civil legislation.

NOTE: A hand-held or plumbed-in extinguisher has a primary purpose of providing an extinguishant that will extend the period of time to enable the extrication of the automobile occupant/s in the event of a fire.

1.1 HAND-HELD FIRE EXTINGUISHERS:

- (a) Each hand-held fire extinguisher must be secured using a metal bracket attached to the *Automobile* with only high tensile bolts or equivalent fasteners and/or sufficient clamp/s and must remain restrained under a deceleration or acceleration of 25g; and
- (b) Must be capable of removal by the driver (or crew, where applicable) while seated in their normal respective position for competition with safety harness unfastened, unless varied by specific category regulations, and without the aid of tools.

1.2 PLUMBED-IN FIRE EXTINGUISHERS:

Each plumbed-in fire extinguisher must be fitted in accordance with the *Code* Appendix J – Article 253 – Safety Equipment at www.fia.com/regulation/category/123 and with attention to the following:

- (a) Each extinguisher container must be adequately protected and may be situated within the cockpit or luggage compartment. If situated in the luggage compartment it must be at least 300mm from the outer edge of the bodywork in all horizontal directions.
- (b) The container must be secured by a minimum of 2 screw-fastened metallic straps and the securing system must be able to withstand a deceleration of 25g.
- (c) Anti-torpedo tabs must be fitted.
- (d) All extinguishing equipment must withstand fire, including the attachments of lines and nozzles.
- (e) The *Driver* (and co-driver where applicable) must be able to trigger the extinguishing system manually when seated normally with their safety harnesses fastened and the steering wheel in place.
- (f) A means of triggering from the outside must be provided in the location of the external battery isolation (master) switch. It must be marked with a letter "E" in red inside a white circle of at least 10 cm diameter with a red edge.
- (g) Each plumbed-in fire extinguisher must be in an active, armed or ready to use state when the *Automobile* is in use. Each active, armed or ready to use state mechanism must be readily accessible and able to be visually identified by the *Driver* (i.e. the arming device for an electronic activation system must be visible to the *Driver*).

1.3 OTHER EXTINGUISHERS

Other extinguishers or fire prevention devices may be fitted in addition to the mandatory requirements as detailed. In each case any other extinguisher that is fitted within the cockpit of an *Automobile* must be secured as a minimum in accordance with the requirements for a hand-held extinguisher.

2. SERVICE AND INSPECTION

- (a) Each hand-held extinguisher should be inspected by a scrutineer at targeted scrutiny, or otherwise prior to *Competition*. This inspection will involve visually checking the unit and its mountings for damage and corrosion, checking the pressure of the contents via an installed gauge, and inverting and shaking the container to check for settling of the extinguishant. Where practical, it is recommended the extinguisher be weighed (mandatory where no gauge is installed).

The following information must be visible on each extinguisher:

- (i) capacity;
 - (ii) type of extinguishant;
 - (iii) weight or volume of the extinguishant; and
 - (iv) date of manufacture of the extinguisher.
- (b) Each AS1841 standard fire extinguisher must be serviced every three years in accordance with AS1851 for a fire extinguisher in an adverse operating environment. If the extinguisher is compliant with another acceptable standard, it must be serviced every two years. This servicing must be undertaken in accordance with the procedures laid out by the manufacturer and/or the relevant standard (e.g. AS1851 for AS1841 extinguishers) and will include a hydrostatic pressure test of the extinguisher body. A report from the servicing agent must be supplied to a scrutineer on demand as proof of a service being completed. A service tag will not be accepted as proof of the extinguisher having been serviced.
- (c) Each fire extinguisher which is homologated by the *FIA* must be serviced either by the manufacturer or their agent no more than two years after either the date of filling or the date of the last service. This servicing must be undertaken in accordance with the procedures laid out by the manufacturer and/or the relevant standard.

3. AUTOTEST EVENTS

In accordance with relevant *Event* regulations.

4. SPEED EVENTS, DRIFTING AND RACE EVENTS

Each *Automobile* must be fitted with a fire extinguisher(s) in accordance with Table H-1.

The fitment of an “on-board” extinguishing system homologated by the *FIA* will be an acceptable alternative to the fitment of a separate extinguisher.

5. RALLY/ROAD EVENTS

Each *Automobile* must be fitted with a hand-held fire extinguisher/s in accordance with Table H-1, and in addition must be equipped as follows:

- (a) In an *International Competition* each *Automobile* must comply with the current *FIA Code* for fire extinguishers.
- (b) In an Australian Rally Championship *Event* each *Automobile* in the ARC class/es must be equipped with a plumbed-in fire extinguisher system in accordance with those permitted for Rally use in *FIA* Technical List No. 16 or *FIA* Technical List No. 52 and fitted in accordance with *FIA Code* Appendix J. Article 253. However where a *Driver* is competing in their home State² in an *Automobile* manufactured prior to January 2000, the *Automobile* will be exempt from this requirement.
- (c) In a *State Competition* an *Automobile* manufactured after 1 January 2000³ must be equipped with a plumbed-in fire extinguisher system approved by the *FIA*¹.

NOTES:

¹ Plumbed-in fire extinguisher systems that are in accordance with those permitted for *Rally* use in *FIA* Technical List No. 16 or *FIA* Technical List No. 52 and fitted in accordance with *FIA Code* Appendix J. Article 253.

It is highly recommended that each *Automobile* in a *State Competition* or lower status *Event* is also fitted with a compliant *FIA* extinguisher system.

² Where in a particular year there is no round of the ARC in the driver's home state, a driver may nominate another State to be his home State.

³ This date refers to the original date of manufacture of the *Automobile*, and not the date on which it was built as a *Rally Automobile*.

(d) For each type of rally/road event, refer Table H-1.

NOTE: It is highly recommended that each new *Automobile* built for Rally/Road is equipped with an extinguisher system compliant, for *Rally*, with *FIA* Technical List No.16 or *FIA* Technical List No. 52.

6. OFF ROAD EVENTS

Each *Automobile* must be fitted with hand held fire extinguisher/s in accordance with Table H-1.

It is highly recommended for each *Automobile* to be fitted with a Plumbed-In Fire Extinguisher as per Article 1.2.

The use of an SFI Specification On-Board Fire Suppression system is permitted.

7. ELECTRIC VEHICLES

Each Electric Vehicle must be fitted with a fire extinguisher/s in accordance with Table H-1.

Hand held Extinguisher/s or Plumbed – In Extinguisher systems with an extinguishing medium proven to not create a conductive atmosphere and in compliance with the *FIA* Standards are highly recommended for an EV (i.e FX G-Tec, Novec 1230, 4F Universal). More than one type of fire extinguisher may be necessary to cope with the different types of flammable components.

8. CIRCUIT RACE

Each *Automobile* must be fitted with a fire extinguisher in a *Circuit Race* as follows:

8.1 National Championship, Cup, Trophy, Challenge or Series:

A plumbed-in fire extinguisher system in accordance with *FIA* Technical List No. 16 or *FIA* Technical List No. 52 and fitted in accordance with *FIA* Code Appendix J. Article 253.

8.2 National, State and Club Competition:

A hand-held extinguisher in accordance with Table H1; or

A plumbed-in fire extinguisher system in accordance with *FIA* Technical List No. 16 or *FIA* Technical List No. 52 and fitted in accordance with *FIA* Code Appendix J. Article 253.

TABLE H-1

MINIMUM HAND-HELD EXTINGUISHER STANDARDS / REQUIREMENTS

Event type	Hand-held extinguisher standard	Minimum total capacity ¹
Autotest	In accordance with relevant <i>Event</i> regulations	
Speed including Drifting	AS1841.5 – ABE Powder or FIA Standard	1kg
Off Road	AS1841.5 – ABE Powder or FIA Standard	2kg in accordance with the fitment requirements of Article 1.1; and 2kg of additional extinguishant mounted in accordance with Article 1.1(a). The requirements of Article 1.1 (b) are not applicable in relation to the mounting of the additional extinguishant.
Special Stage Rally/S2 Rally Sprint	AS1841.5 – ABE Powder or FIA Standard	2kg

S1 Rally Sprint (venue unmanned by marshals)	AS1841.5 – ABE Powder or FIA Standard	1kg
Other Rally/Road Events	In accordance with relevant <i>Event</i> regulations	
Circuit Race	AS1841.5 – ABE Powder or FIA Standard	1kg
Electric Vehicles ALL Events	AS1841.5 – ABE Powder or FIA Standard	2kg

¹ The minimum capacity of 2kg may be made up by the fitment of 2 x 1kg extinguishers.

AUSTRALIAN STANDARD EXTINGUISHERS

Extinguisher	Extinguisher Standard	Notes
Powder ABE	AS 1841.5	General Purpose, suitable for most fire types. This Australian Standard extinguisher is the most common extinguisher that is available in 1kg and 2kg sizes. Other Australian Standard extinguisher types (i.e. AS1841.2 FOAM) are not readily available in 1 kg and 2 kg sizes.

FIA STANDARD EXTINGUISHERS

In each *Event* type it is permitted to equip a hand held extinguisher that complies with the *FIA* Manual Extinguisher regulations, instead of the use of an AS1841.5 standard extinguisher. Each *FIA* Manual Extinguisher must be of the minimum capacity, fitted and maintained in accordance with the *FIA* regulations as published in the *Code* with specific reference to Appendix J – Article 253 – Safety Equipment at www.fia.com/regulation/category/123.



R RACER INDUSTRIES

WWW.RACERINDUSTRIES.COM.AU

1300 722 374

AUSTRALIA'S LEADING AUTHORITY ON MOTORSPORT
FIRE EXTINGUISHERS AND SAFETY EQUIPMENT

STOCKING THE WORLDS LEADING BRANDS,
MASSIVE INVENTORY

EXTINGUISHERS TO SUIT ALL CARS

MECHANICAL, ELECTRICAL AND HAND HELD
EXTINGUISHERS

AUTHORISED SERVICE AGENT
LIFELINE - SPARCO - FEV
CONTACT SERVICING@RACERINDUSTRIES.COM.AU

NATIONWIDE EXPRESS DELIVERY

sparco

lifeline
Fire & Safety Supplies Ltd